

별표 1. (제15조 비상조명등의 형식승인 및 제품검사의 기술기준 관련)

배 광 번 호 표

조도(lx) 부착높이(m) 배광번호		0.5			1			2		
		2	3	4	2	3	4	2	3	4
A	1	2.8	3.6	4.1	2.4	2.9	3.2	2.0	2.2	2.1
	2	2.9	3.9	4.7	2.7	3.4	3.8	2.3	2.7	2.9
	3	3.1	4.2	5.1	2.8	3.8	4.4	2.5	3.2	3.5
	4	3.2	4.5	5.6	3.0	4.1	4.9	2.8	3.6	4.1
	5	3.3	4.7	5.9	3.1	4.4	5.4	2.9	3.9	4.7
	6	3.3	4.8	6.1	3.2	4.5	5.6	3.0	4.1	4.9
	7	3.4	4.8	6.2	3.2	4.6	5.7	3.1	4.2	5.1
	8	3.4	4.9	6.3	3.3	4.7	5.9	3.1	4.3	5.3
	9	3.4	4.9	6.4	3.3	4.8	6.1	3.2	4.5	5.6
	10	3.4	5.0	6.5	3.3	4.8	6.2	3.2	4.6	5.7
B	11	3.3	3.8	4.1	2.7	2.9	2.9	2.1	2.0	1.2
	12	3.8	4.5	5.0	3.1	3.6	3.8	2.5	2.7	2.5
	13	4.2	5.1	5.8	3.5	4.1	4.5	2.9	3.2	3.3
	14	4.7	5.8	6.6	4.0	4.8	5.3	3.3	3.8	4.1
	15	5.2	6.5	7.5	4.5	5.5	6.2	3.7	4.5	4.9
	16	5.4	6.9	8.0	4.7	5.8	6.6	4.0	4.8	5.3
	17	5.8	7.3	8.4	4.9	6.2	7.1	4.2	5.1	5.8
	18	6.1	7.6	8.9	5.2	6.5	7.5	4.4	5.4	6.2
	19	6.5	8.0	9.4	5.4	6.9	8.0	4.7	5.8	6.6
	20	6.9	8.4	9.9	5.8	7.2	8.4	4.9	6.1	7.1
C	21	3.6	4.0	4.0	2.8	2.8	2.3	2.0	1.5	-
	22	4.3	4.8	5.1	3.4	3.6	3.4	2.5	2.4	1.7
	23	5.0	5.7	6.1	4.0	4.4	4.5	3.1	3.2	2.9
	24	5.7	6.7	7.3	4.6	5.3	5.6	3.6	4.0	4.0
	25	6.5	7.7	8.6	5.3	6.2	6.7	4.3	4.8	5.0
	26	6.9	8.3	9.2	5.7	6.7	7.3	4.6	5.3	5.6

조도(lx) 부착높이(m) 배광번호		0.5			1			2		
		2	3	4	2	3	4	2	3	4
C	27	7.3	8.8	9.9	6.1	7.2	7.9	5.0	5.7	6.1
	28	7.8	9.4	10.7	6.5	7.7	8.5	5.3	6.1	6.7
	29	8.3	10.1	11.5	6.9	8.3	9.2	5.7	6.7	7.3
	30	8.3	10.7	12.2	7.3	8.8	9.9	6.1	7.2	7.9
D	31	2.7	2.5	1.7	1.8	1.0	-	0.8	-	-
	32	3.4	3.4	3.0	2.4	2.0	0.8	1.5	-	-
	33	4.1	4.3	4.2	3.0	2.9	2.4	2.1	1.5	-
	34	4.9	5.3	5.4	3.7	3.8	3.6	2.7	2.5	1.7
	35	5.8	6.4	6.7	4.5	4.8	4.8	3.3	3.4	3.0
	36	6.3	7.0	7.4	4.9	5.3	5.4	3.7	3.8	3.6
	37	6.9	7.6	8.2	5.3	5.8	6.0	4.1	4.3	4.2
	38	7.4	8.3	8.9	5.8	6.4	6.7	4.4	4.7	4.8
	39	8.1	9.1	9.8	6.3	7.0	7.4	4.9	5.3	5.4
	40	8.8	9.9	10.7	6.9	7.6	8.2	5.3	5.8	6.0